



Accessories

SFP + XFD Transceiver Modules

SFP + XFD Transceiver Modules		
Part No.	Order No.	Description
M-FAST SFP-MM/LC	943 865-001	100BASE-FX, 5 km 50/125 μm MM, 4 km 62.5/12.5 μm MM
M-FAST SFP-MM/LC EEC	943 945-001	100BASE-FX, 5 km 50/125 μm MM, 4 km 62.5/12.5 μm MM
M-FAST SFP-SM/LC	943 866-001	100BASE-FX, 25 km 9/125 μm SM
M-FAST SFP-SM/LC EEC	943 946-001	100BASE-FX, 25 km 9/125 μm SM
M-FAST SFP-SM+/LC	943 867-001	100BASE-FX, 25–65 km 9/125 μm SM
M-FAST SFP-SM+/LC EEC	943 947-001	100BASE-FX, 25–65 km 9/125 μm SM
M-FAST SFP-LH/LC	943 868-001	100BASE-FX, 55–140 km 9/125 μm SM
M-FAST SFP-LH/LC EEC	943 948-001	100BASE-FX, 55–140 km 9/125 μm SM
Gigabit Ethernet		
Part No.	Order No.	Description
M-SFP-SX/LC	943 014-001	1000Base-SX, 550 m 50/125 μm MM, 275 m 62.5/125 μm MM
M-SFP-SX/LC EEC	943 896-001	1000Base-SX, 550 m 50/125 μm MM, 275 m 62.5/125 μm MM
M-SFP-LX/LC	943 015-001	1000Base-SX, 550 m 50/125 μm MM, 550 m 62.5/125 μm MM, 20 km 9/125 μm SM
M-SFP-LX/LC EEC	943 897-001	1000Base-SX, 550 m 50/125 μm MM, 550 m 62.5/125 μm MM, 20 km 9/125 μm SM
M-SFP-LH/LC	943 042-001	1000Base-LX, 16–80 km 9/125 μm SM-LH
M-SFP-LH+/LC	943 049-001	1000Base-LX, 44–120 km 9/125 μm SM-LH
Gigabit Ethernet Bi-Directional (Single Fiber Strand)		
Part No.	Order No.	Description
M-SFP-BIDI-Bundle LX/LC EEC	943 974-101	1000Base-SX, 20 km 9/125 μm SM
M-SFP-BIDI-Bundle LH/LC EEC	943 975-101	1000Base-LX, 23–80 km 9/125 μm SM-LH
10Gigabit Ethernet		
Part No.	Order No.	Description
M-XFP-ZR/LC	943 921-001	10GBASE-SX, 40–80 km 9/125 μm SM
M-XFP-ER/LC	943 920-001	10GBASE-SX, 10–40 km 9/125 μm SM
M-XFP-LR/LC	943 919-001	10GBASE-SX, 2–10 km 9/125 μm SM
M-XFP-SR/LC	943 917-001	10GBASE-SX, 33 m 50/125 μm MM or 300 m w/modal bandwidth 2000 [MHz x km] fiber



Power Supplies and Programming/Configuration Tools

Power Supplies		
Part No.	Order No.	Description
RPS30	943 662-003	24 VDC power supply unit 1.3A
RPS80 EEC	943 662-080	24 VDC power supply unit 3.0A, –25°C up to +70°C
RPS120 EEC	943 662-120	24 VDC power supply unit 4.5A, –25°C up to +70°C
RPS60/48V EEC	943 952-001	48 VDC PoE power supply unit 1.25A, –10°C up to +70°C
PSW 5-24	943 008-001	5 VDC Plug-in power supply 0°C up to +40°C



Programming and Configuration Backup		
Part No.	Order No.	Description
ACA 21-USB EEC	943 271-002	USB configuration adapter for storage/backup and device replacement of (managed) OpenRail, MICE, MACH switches and EAGLE firewalls
ACA21-M12 EEC	943 913-002	USB configuration adapter for storage/backup and device replacement of (managed) Octopus switches devices
ACA11 EEC	943 751-002	Similar to above ACA adapters, but communication via the RS232 interface
Serial/Terminal Cable	943 301-001	Terminal cable for managing and configuring managed switches via the RS232 interface

